

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



552981

(43) International Publication Date
21 October 2004 (21.10.2004)

PCT

(10) International Publication Number
WO 2004/090306 A1

(51) International Patent Classification⁷: F02B 75/38,
75/04

(21) International Application Number:
PCT/GB2004/001483

(22) International Filing Date: 5 April 2004 (05.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0308524.8 12 April 2003 (12.04.2003) GB

(71) Applicant: GALVIN, George, Frederic [GB/GB]; 9
Christchurch Road, Sidcup, Kent DA15 7HG (GB).

(74) Agent: PRATT, David, Martin; David Pratt & Co, 7
Parkhill Road, Sidcup, Kent DA15 7NW (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: PISTON



(57) Abstract: A piston (1) incorporates spring means (8) acting, in use, between the piston and an associated connecting rod (4) so as to bias the connecting rod away from the crown (2) of the piston. The spring means (8) is constituted by a pair of disc springs (9) whose circumferential edge portions are supported and separated by a substantially annular support member (10, 11), the spring means being located substantially in the region of the piston crown (2). A carrier (5) is positioned within the piston, the carrier being slidably mounted within the piston for axial movement relative thereto, and being connected to the connecting rod (4) in such a manner that the spring means (8) permits the crown (2) to move axially relative to the carrier (5).

WO 2004/090306 A1